

tesa® extra Power Perfect – 56339, 56341, 56342, 56343, 56344

tesa® extra Power Perfect is a powerful high quality acrylic coated cloth tape. It is based on a 145 mesh woven rayon fabric backing and a natural rubber adhesive. It has a high adhesion even on rough surfaces and an excellent tensile strength.

Main Application

- For all professional solutions like handicrafts, fastening, bundling, strengthening and marking
- For permanently high resilience and long-term results
- Very strong and perfect adhesive power, also on rough surfaces
- Tear-resistant but tearable by hand
- Can be written on
- Straight tear edges longitudinal and horizontal
- Wide range of colors
- Formable

Technical Data & Properties

Backing material	Acrylic-coated cloth
Total thickness	310 µm
Type of adhesive	Natural rubber
Adhesion to steel	3.3 N/cm
Elongation at break	13%
Tensile strength	100 N/cm
Mesh	145 count per square inch
Temperature resistance (30min)	130 °C
Hand tearability	●●●●
Straight tear edges	●●●●
Suitable for die cutting	yes
Abrasion resistance	●●●●
Water resistance	●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Additional Information & Pictures



56339, 56341, 56342, 56343, 56344

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.