NiMH Battery Charger (CHVCM4E/CHVCM4)

Download Instructions (Americas) Download Instructions (Rest of World)

Product Detail:

Designation: Value Charger / Maxi Charger

Model: CHVCM4E / CHVCM4

Color: Black

Charge Capability: "AA" (2) or (4) / "AAA" (2) or (4)

"AA" (2) and "AAA" (2) Simultaneously

Note: Please note battery orientation diagrams

in the instructions.

Charging Times:

Estimated Battery Capacity (estimated) (NiMH) (mAh) (time) 1300-2000 AA

6-8 hrs AA 2000-2300 8-10 hrs AAA 500-800 5-7 hrs

Shutoff Mechanism: Delta V Detection

Timer Control: 11 hours

Charging Current: "AA" 260-300mA

"AAA" 120-150mA

Trickle Charge: None

Input Rating (US): 110-127VAC, 50-60Hz, 6W

Input Rating: 100-240VAC, 50-60Hz, 6W

Typical Weight: 107 grams

Dimensions (mm): 115 x 71 x 62 (H x L x W) Safety Features: Reverse Polarity Protection

> Bad Battery Detection Primary Battery Detection Delta V Charging Cut Off

Safety Timer to Prevent Overcharge

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication. Contents herein do not constitute a warranty.

ENHANCED COMMUNICATION

 Multiple colored LED lights indicate charge status











(PULSING)



 Limits damage to batteries from overcharge



SAFETY TIMER

 Ensures charger is not active for extended periods of time



Before Using Your Charger:

NIMH BATTERY AA.AAA

Please read all instructions and cautionary markings on the battery charger, batteries, and device.

Best used with *Energizer*_® NiMH batteries.