

# Scotch®

## Rough Surface Painter's Tape

### #2060

FOR ROUGH TEXTURED SURFACES

USE ON  
CONCRETE, BRICK, STUCCO,  
ROUGH WOOD &  
LACQUER COATING

5-DAY  
CLEAN REMOVAL

VERY  
STRONG  
ADHESIVE

Scotch® Rough Surface Painter's Tape has a very strong adhesive to handle the roughest of surfaces. Brick, concrete, stucco and rough wood get the protection they need to do the job. Also recommended for use on lacquer coating. Holds strongly and removes easily without leaving sticky residue behind. Rough project? Use a tough tape.



### PHYSICAL PROPERTIES

CAT#	ADHESION TO STAINLESS STEEL 12"/min oz/in	TENSILE lbs/in	ELONGATION %	CALIPER mils	COLOR	BACKING	ADHESIVE TYPE	DAYS CLEAN REMOVAL
<b>2060</b>	<b>34</b>	<b>22</b>	<b>11</b>	<b>6.6</b>	<b>GREEN</b>	<b>CREPE</b>	<b>RUBBER</b>	<b>5</b>

### KEY BENEFIT

This tape is ideal for rough-textured, non-damageable surfaces like concrete, brick, stucco and rough wood. Also designed to work on lacquer coating.

### APPLICATION

For great paint results, make sure the surface is clean, dry and dust-free so that the tape sticks properly. Next, apply the tape onto the surface while pressing down firmly as you go. Lastly, let the tape set for about 30 to 60 minutes before painting.

### REMOVAL

Wait until the paint is dry to the touch before removing the tape. Lift the tape up by slowly pulling it back on itself, then removing at a 45-degree angle.

### STORAGE

70°F, 50% relative humidity, avoid storing at >120° F

### WIDTHS AVAILABLE

18mm, 24mm, 36mm, 48mm

### UV RESISTANT

Up to 5 days indoor and 3 days outdoor

**IMPORTANT NOTICE:** All statements, technical information and recommendations herein are based on tests 3M believes to be reliable. 3M does not warrant or guarantee the accuracy or completeness of this information. THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE: 3M's only obligation shall be to replace such quantity of this 3M product proved to be defective. User is responsible for determining whether this 3M product is fit for a particular purpose and suitable for user's method of application. Because there are many factors that can affect the use and performance of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate this product to determine whether it is fit for a particular purpose, is suitable for the user's method of application, and meets the user's performance specifications and expectations.

**Limitation of Liability:** 3M SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGES, WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL (INCLUDING BUT NOT LIMITED TO LOST PROFITS, BUSINESS, OR REVENUES) ARISING OUT OF THE USE OF OR INABILITY TO USE THIS 3M PRODUCT, WARRANTY, OR STRICT LIABILITY. No statement or recommendation not contained herein shall have any force or effect unless contained in an agreement signed by a 3M officer.



Construction and Home Improvement Markets Division  
3M Center, Building 223-4S-02  
St. Paul, MN 55144-1000 USA

© 3M 2019. All rights reserved. 3M and Scotch are trademarks of 3M. Please recycle. Printed in U.S.A. 70-0717-2648-6