1/5 Creation Date: August 4, 2010

Safety data sheet for chemical products

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: SX-101-10 Blue [JETSTREAM 101]

Manufacture's name : MITSUBISHI PENCIL CO.,LTD.

Address : 5-23-37, HIGASHIOHI, SHINAGAWA, TOKYO, JAPAN Telephone number : 03-3458-6281 Telefax number : 03-3450-0363

Telex number : 2422337 MBPENC J.

Creation Date : August 4, 2010

Revision Date

File No. : 061344A Rev.2.5.01.01

2. COMPOSITION/INFORMATION ON INGREDIENTS

The chemical product is a substance or a preparation: Preparation

Chemical nature: Component parts : Ink

| Chemical or generic name | CAS No. | TSCA | EINECSNo. | Concentration range (wt%) |
|--------------------------|---------------------------|------------|------------|------------------------------|
| Glycol ether | 56539-66-3 | Registered | 2602524 | 50- 80 |
| Coloring agents | Registered | Registered | Registered | 10- 30 |
| Additives | Registered | Registered | Polymer | 10- 30 |
| Resins | Registered | Registered | Polymer | < 10 |
| Polypropylene glycol | Registered | Registered | Polymer | < 10 |
| 1,2-Propanediol | 57 - 55 - 6 | Registered | 2003380 | < 10 |

Other parts : Other parts are excluded from 'chemical substances'.

3. HAZARDS IDENTIFICATION

Most important hazards : Not available. Specific hazards : Not available.

4. FIRST-AID MEASURES

Inhalation:

Not applicable.

(Due to its low vapor pressure. Inhalation is unlikely at room temperature.)

Skin contact:

Wash skin with soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention, if needed. Thoroughly clean and dry contaminated clothing and shoes before reuse.

Eye contact:

Flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion:

If swallowed, seek medical advice, and show the MSDS to the physician then.

[Ink quantity of refill(SXR-72-10) : about 0.22g]

2/5 Creation Date: August 4, 2010

5. FIRE-FIGHTING MEASURES

Fire and explosion measures : Slight fire hazard.

Extinguishing media:

Suitable : regular dry chemical, carbon dioxide, water, regular foam.

Large fires : Use regular foam or flood with fine water spray.

Fire fighting : Move container from fire area if it can be done without risk.

Use extinguishing agents appropriate for surrounding fire. Avoid inhalation of material or combustion by-products.

Stay upwind and keep out of low areas.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Not available.

Environmental precautions: Do not wash away into shower or water way.

Methods for cleaning up : Take / Soak up with absorbent.

: In accordance with national, state and local regulations.

7. HANDLING AND STORAGE

Store and handle in accordance with all current regulations and standards.

Keep separated from incompatible substances.

Handling:

Technical measures : Don't swallow ink.

: Don't shake.

Keep out of the reach of children. : Avoid contact with skin and eyes.

Precautions : Not available.

Safe handling advice

: Not available.

Storage:

Technical measures : Keep away from oxidizing materials, ignition sources and

high temperature.

Storage condition : Avoid direct sunlight.

: Do not leave the products in high temperature space.

: Recommended temperature: 0-30 C.

Incompatible products : (Information of components.)

oxidizing materials, organic peroxides Glycol ether

oxidizing materials Coloring agent / Resin / Polypropylene glycol

strong oxidizers Additive

acids, bases, combustible materials, halo carbons, metals,

1,2-Propanediol

metal salts, oxidizing materials, reducing agents

Packaging materials : Not applicable. 3/5 Creation Date: August 4, 2010

8. EXPOSURE CONTROL / PERSONAL PROTECTION

Engineering measures : Not required.

Control parameters (Information of components.)

| OSHA | Not available. | |
|-------|----------------------------|-------|
| ACGIH | 10mg/m3 TWA(Nuisance dust) | Resin |
| EC | Not available. | |

Personal protective equipment : Not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

[]: Information of components.

Physical state and form : High viscous liquid.

Color : Blue.
Odor : None odor.
pH : Not applicable.

Boiling point : Not available. [Glycol ether/ 174 C]

Melting point : Not available.

Flash point : Not available. [Glycol ether/ 68 C] Autoignition temperature : Not available. [Glycol ether/ 395 C]

Explosion limits : Not applicable.

Density : Not available.

Vapor density (air=1) : Not available. [Glycol ether/ 4.1]

Solubility in water : Not available. Evaporation rate : Not available. Volatile : 51-54%

10. STABILITY AND REACTIVITY

Stability : Stability.

Hazardous reactions : Will not occur.

Conditions to avoid : Avoid heat, flames, sparks and other sources of ignition.

Avoid contact with incompatible materials.

Materials to avoid : (Information of components.)

oxidizing materials, organic peroxides Glycol ether

oxidizing materials Coloring agent / Resin /

Polypropylene glycol

strong oxidizers Additive

acids, bases, combustible materials, halo carbons, metals, 1,2-Propanediol

metal salts, oxidizing materials, reducing agents

Hazardous decomposition products : (Information of components.)

oxides of carbon, water common decomposition products

oxides of nitrogen, sulfur. Coloring agent

toxic and/or hazardous gases, miscellaneous Resin

decomposition products.

11.TOXICOLOGICAL INFORMATION

(Information of components)

Acute toxicity

| Ingestion LD50 | 4300mg/kg-Rat | Glycol ether |
|-----------------|-------------------|----------------------|
| | ≥5000mg/kg-Rat | Coloring agent |
| | >3000mg/kg-Rat | Resin |
| | 57000mg/kg-Rat | Polypropylene glycol |
| 30 | 20000mg/kg-Rat | 1,2-Propanediol |
| Inhalation LC50 | Not available. | |
| Skin LD50 | >2000mg/kg | Glycol ether |
| | 20800mg/kg-Rabbit | 1,2-Propanediol |

Local effects Irritant; eye Resin

Chronic toxicity and long term toxicity

Repeated or prolonged contact may cause skin sensitization.

Lungs may be affected by repeated or prolonged exposure at very high

1,2-Propanediol Carbon Black

concentrations.

Signs and Symptoms of overexposure and aggravated by exposure

| Inhalation | irritation | Coloring agent / Resin |
|--------------|--|-----------------------------------|
| | nausea, headache | 1,2-Propanediol |
| Skin contact | inflammation | Glycol ether |
| | irritation | Coloring agent / Additive / Resin |
| | | Polypropylene glycol |
| | irritation, allergic reaction | 1,2-Propanediol |
| | irritation | Glycol ether / Coloring agent / |
| | | Additive / Resin / Polypropylene |
| Eye contact | | glycol |
| | irritation, pain | 1,2-Propanediol |
| | laxative effect, dark-colored | Coloring agent |
| Ingestion | urine | |
| | nausea, vomiting | Polypropylene glycol |
| | allergic reaction, vomiting | 1,2-Propanediol |
| | * ************************************ | |

Specific effects Not available.

12. ECOLOGICAL INFORMATION

Not available.

13. DISPOSAL CONSIDERATIONS

Waste from residues : Disposal in accordance with all current regulations and standards.

Contaminated packaging: Not applicable.

14. TRANSPORT INFORMATION

HS Code : 960810

5/5 Creation Date: August 4, 2010

15. REGULATORY INFORMATION

Regulations (Information of components)

Hazardous chemicals (OSHA HCS) : Not available.

EU labeling Xi;R36/38 : Additive

CANADA Hazardous Products Act - Ingredient Disclosure List

1%over : 1,2-Propanediol

Hazard and safety information

Products are manufactured in accordance with ISO 8124-3 " Safety of Toys - Part 3"

16. OTHER INFORMATION

This sheet completes the technical sheet of use but it doesn't replace it. The information contained in this sheet are based knowledge of the products at the data: (August 4, 2010). They are given quite sincerely. Moreover the attention of the users is drawn on the risks possibly taken, when a product is used for other utilization than these which it is intended.