



# Exterior Surface Painter's Tape

## #2097

**FOR SMOOTH AND SEMI-SMOOTH EXTERIOR SURFACES**

**USE ON GLASS, METAL, VINYL, PAINTED WOOD & HUMID CONDITIONS**

**10-DAY CLEAN REMOVAL** | **VERY STRONG ADHESIVE**

Weather the elements with Scotch® Exterior Surface Painter's Tape. Designed to stand up to wind, rain, humidity and sun. This innovative poly tape conforms to curves, tears straight for fast cornering and removes easily without tearing, slivering or leaving sticky residue. For smooth and semi-smooth metal, vinyl, painted wood and glass. Works hard when it's brutal out.



### PHYSICAL PROPERTIES

CAT#	ADHESION TO STAINLESS STEEL 12"/min oz/in	TENSILE lbs/in	ELONGATION %	CALIPER mils	COLOR	BACKING	ADHESIVE TYPE	DAYS CLEAN REMOVAL
<b>2097</b>	<b>36</b>	<b>10</b>	<b>400</b>	<b>5.4</b>	<b>YELLOW</b>	<b>POLYETHYLENE</b>	<b>RUBBER</b>	<b>10</b>

### KEY BENEFIT

A weatherproof, innovative poly-tape for glass, vinyl, metal and painted wood. Designed for exterior surfaces and stands up to the elements. Conforms to curves, tears straight.



### APPLICATION

For great paint results, make sure the surface is clean, dry and dust-free so that the tape sticks properly. Next, apply the tape onto the surface while pressing down firmly as you go. Lastly, let the tape set for about 30 to 60 minutes before painting.

### REMOVAL

Wait until the paint is dry to the touch before removing the tape. Lift the tape up by slowly pulling it back on itself, then removing at a 45-degree angle.

### STORAGE

70°F, 50% relative humidity, avoid storing at >120° F

### WIDTHS AVAILABLE

36mm, 48mm

### UV RESISTANT

Up to 10 days outdoor

**IMPORTANT NOTICE:** All statements, technical information and recommendations herein are based on tests 3M believes to be reliable. 3M does not warrant or guarantee the accuracy or completeness of this information. THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE: 3M's only obligation shall be to replace such quantity of this 3M product proved to be defective. User is responsible for determining whether this 3M product is fit for a particular purpose and suitable for user's method of application. Because there are many factors that can affect the use and performance of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate this product to determine whether it is fit for a particular purpose, is suitable for the user's method of application, and meets the user's performance specifications and expectations.

**Limitation of Liability:** 3M SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGES, WHETHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL (INCLUDING BUT NOT LIMITED TO LOST PROFITS, BUSINESS, OR REVENUES) ARISING OUT OF THE USE OF OR INABILITY TO USE THIS 3M PRODUCT, WARRANTY, OR STRICT LIABILITY. No statement or recommendation not contained herein shall have any force or effect unless contained in an agreement signed by a 3M officer.



**Construction and Home Improvement Markets Division**  
3M Center, Building 223-4S-02  
St. Paul, MN 55144-1000 USA

© 3M 2019. All rights reserved. 3M and Scotch are trademarks of 3M. Please recycle. Printed in U.S.A. 70-0717-2647-8